

UNISYNT ZX

SAE 75W/90 GL-4+5

Fully synthetic gear oil for manual gearboxes of heavy goods vehicles, cars and axle drives. GL-4+5.

Description

GEAR OIL UNISYNT ZX SAE 75W/90 is a universal, fully synthetic, high-performance gear oil. The fully synthetic base fluid guarantees optimum low-temperature behaviour as well as extremely comfortable shifting. The latest generation of high-quality additives means that UNISYNT ZX SAE 75W/90 is ideal for use in both manual gearboxes and in axles subject to high loads.

Advantages

- fully synthetic, high-performance gear oil
- reliable power reserves under extreme conditions
- reliable wear protection
- high oxidation and shear stability

Field of application

GEAR OIL UNISYNT ZX SAE 75W/90 enables a broad usage spectrum. This high-performance gear oil is ideal for both manual gearboxes in lorries and for axles subject to high loads. Thanks to its universal application, only one grade is necessary. This simplifies storage and minimises the risk of confusion.

Application

Fully synthetic gear oil for manual gearboxes and axle drives in heavy goods vehicles and cars. GL-4+5.

Notes

Please adhere to the manufacturer's instructions.

Specifications

API GL-4/5; API MT-1; MIL-PRF-2105E; SAE J2360;
ARVIN MERITOR 076-N; MACK GO-J; MAN 341 Z2; MAN 342 M3;
MAN 342 S1; MB-Approval 235.8; SCANIA STO 1:1G;
SCANIA STO 2:0 A FS; VOLVO 97312; ZF TE-ML-02B;
ZF TE-ML-05A; ZF TE-ML-07A; ZF TE-ML-08; ZF TE-ML-12L;
ZF TE-ML-12N; ZF TE-ML-16F; ZF TE-ML-17B; ZF TE-ML-19C;
ZF TE-ML-21A

Safety + Performance

IVECO 18-1805 RA S1; MAN 341 E3; MAN 341 GA2;
SCANIA STO 1:0

Technical data

Properties	Unit	Test according to	Values
Colour			yellow
Density at 20 °C	g/cm ³	ASTM D4052	0.865
Viscosity at 40 °C	mm ² /s	DIN 51562-1	103
Viscosity at 100 °C	mm ² /s	DIN 51562-1	15.4
Viscosity index		DIN ISO 2909	157
Pourpoint	°C	ASTM D5950	-60
Flash point C.O.C.	°C	DIN EN ISO 2592	>200
Brookfield	°C / mPa·s	ASTM D 2983	-40 / 61500

The above information corresponds to the current state of our knowledge. We reserve the right to make changes. The performance characteristics indicated are based on testing and production tolerances standard in this industry. A safety data sheet is available.



MOTOREX AG
Bern-Zürich-Strasse 31
CH-4901 Langenthal
Tel. +41 (0)62 919 75 75
info@motorex.com, www.motorex.com