

TWO STROKE 2T

Synthetic motor oil for two-stroke lightweight motorbikes

Description

TWO STROKE 2 T is a synthetic motor oil for lightweight motorbikes.

Advantages

- synthetic
- minimal smoke formation (low smoke)
- for pre-mix and separate lubrication
- official JASO FC approval

Field of application

TWO STROKE 2T is recommended for a wide range of lightweight motorbikes that do not have any particular specifications. It can be used for pre-mix and separate lubrication (mixing ratios in accordance with manufacturer's recommendation).

Notes

Please observe the manufacturer's instructions.

Specifications

JASO FC; API TC; ISO-L-EGC



PRODUCT MEETING JASO M 345
COMPANY GUARANTEEING THIS FC PERFORMANCE:
BUCHER AG

Technical data

Properties	Unit	Test according to	Values
Colour			green
Density at 20 °C	g/cm ³	ASTM D4052	0.868
Viscosity at 40 °C	mm ² /s	DIN 51562-1	61.3
Viscosity at 100 °C	mm ² /s	DIN 51562-1	9.3
Viscosity index		DIN ISO 2909	132
Pourpoint	°C	ASTM D5950	-33
Flash point C.O.C.	°C	DIN EN ISO 2592	>100
Sulphate residue content	%	DIN EN ISO 6245	0.03
Sulfur	%		0.15
TAN	mg KOH/g	ASTM D 664 DIN 51558-1	0.05
TBN	mg KOH/g	DIN ISO 3771	0.62

The above information corresponds to the current state of our knowledge. We reserve the right to make changes. The performance characteristics indicated are based on testing and production tolerances standard in this industry. A safety data sheet is available.