

FOUR STROKE 4T

SAE 5W/40 JASO MA2

Synthetic blend motor oil for four-stroke motorcycles and scooters

Description

MOTOREX FOUR-STROKE 4T is a synthetic blend, shear-stable motor oil that is also suitable for engines with wet multi-disc clutches.

Advantages

- stable lubricating film
- temperature-stable
- shear-stable (stay-in-grade)

Field of application

MOTOREX FOUR-STROKE 4T is available in three further viscosity classes (10W/40, 15W/50 und 20W/50) and is suitable for a wide range of motorbikes of all kinds without special requirements. Please always observe the manufacturer's specifications regarding viscosity and oil quality.

Dosage

According to manufacturer's specifications

Notes

MOTOREX recommends that you observe the manufacturer's specifications regarding maintenance intervals

Specifications

JASO MA2; API SL; API SJ; API SH; API SG



JASO T 903 : 2016
PERFORMANCE IS GUARANTEED by
BUCHER AG

Technical data

Properties	Unit	Test according to	Values
Colour			yellow-brown
Density at 20 °C	g/cm ³	ASTM D4052	0.851
Viscosity at 40 °C	mm ² /s	DIN 51562-1	88.9
Viscosity at 100 °C	mm ² /s	DIN 51562-1	14.2
Viscosity index		DIN ISO 2909	165.6
Viscosity according to HTHS at 150 °C	mPa·s	CEC-L-36 A-97	≥3.5
Pourpoint	°C	ASTM D5950	-39.7
Flash point C.O.C.	°C	DIN EN ISO 2592	≥200
CCS at	°C / mPa·s	ASTM D 5293	-30 / 6580
Sulphate residue content	%	DIN EN ISO 6245	0.8
NOACK	%	CEC L-40-A-93	8.6
TBN	mg KOH/g	DIN ISO 3771	5.7

The above information corresponds to the current state of our knowledge. We reserve the right to make changes. The performance characteristics indicated are based on testing and production tolerances standard in this industry. A safety data sheet is available.