

SCOOTER 4T

SAE 10W/30 JASO MB

Synthetic 4-stroke motor oil for scooters

Description

A synthetic blend 4-stroke motor oil specifically for scooters. During the development phase, particular attention was paid to the specific requirements of scooters with regard to day-to-day use involving frequent cold starts and high operating temperatures. Ideal for models with injection engines and catalytic converters.

Advantages

- optimal cold-starting properties
- very good wear protection
- ideal for stop-and-go traffic

Field of application

The SCOOTER 4T SAE 10W/30 JASO MB was developed for four-stroke scooters whose manufacturers do not recommend a fully synthetic oil. Ideal for use in stop-and-go traffic.

Specifications

JASO MB; API SL; API SJ; API SH; API SG



JASO T 903 : 2016
PERFORMANCE IS GUARANTEED by
BUCHER AG

Technical data

Properties	Unit	Test according to	Values
Colour			brown
Density at 20 °C		ASTM D4052	0.859
Viscosity at 40 °C	mm ² /s	DIN 51562-1	65.3
Viscosity at 100 °C	mm ² /s	DIN 51562-1	10.3
Viscosity index		DIN ISO 2909	144
Viscosity according to HTHS at 150 °C	mPa·s	CEC-L-36 A-97	≥2.9
Pourpoint	°C	ASTM D5950	-39
Flash point C.O.C.	°C	DIN EN ISO 2592	≥200
CCS at	°C / mPa·s	ASTM D 5293	-25 / 5173
Sulphate residue content	%	DIN EN ISO 6245	0.7
NOACK	%	CEC L-40-A-93	11.8
TBN	mg KOH/g	DIN ISO 3771	6.3

The above information corresponds to the current state of our knowledge. We reserve the right to make changes. The performance characteristics indicated are based on testing and production tolerances standard in this industry. A safety data sheet is available.